



EN 50371 REPORT

REPORT NO.: SE941208L11C

MODEL NO.: SDC-CF10G

ACCORDING: EN 50371:2002

APPLICANT : Summit Data Communications, Inc.

ADDRESS : 526 South Main Street Suite 411, Akron, Ohio,
44311 United States

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No.47, 14th Ling, Chia Pau Tsuen, Linko Hsiang 244,
Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 6 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.



No. 2177-01



TABLE OF CONTENTS

1.	CERTIFICATION.....	3
2.	GENERAL DESCRIPTION OF EUT.....	4
3.	RF EXPOSURE MEASUREMENT.....	5
3.1	INTRODUCTION.....	5
3.2	COMPLIANCE CRITERIA.....	5
3.3	EUT OPERATING CONDITION.....	6
3.4	TEST RESULTS.....	6



1. CERTIFICATION

PRODUCT: SDC-CF10G 802.11g Compact Flash Module with Antenna Connectors

MODEL: SDC-CF10G

BRAND: Summit

APPLICANT: Summit Data Communications, Inc.

TESTED: Jun. 14 ~ Aug. 14, 2006

TEST SAMPLE: Engineering Sample

STANDARDS: EN 50371:2002

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Rennie Wang , **DATE:** Aug. 18, 2006
Rennie Wang

TECHNICAL ACCEPTANCE : Stanley Hsu , **DATE:** Aug. 18, 2006
Responsible for RF Stanley Hsu

APPROVED BY : Gary Chang , **DATE:** Aug. 18, 2006
Gary Chang / Supervisor

2. GENERAL DESCRIPTION OF EUT

2.1. GENERAL DESCRIPTION OF EUT

PRODUCT	SDC-CF10G 802.11g Compact Flash Module with Antenna Connectors
MODEL NO.	SDC-CF10G
SOURCE VOLTAGE	$V_{nom} = 230$ $V_{min} = 207$ $V_{max} = 253$
POWER SUPPLY	3.3Vdc from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
FREQUENCY RANGE	For France: 2400 ~ 2454MHz For other EU countries: 2400 ~ 2483.5MHz
NUMBER OF CHANNEL	For France: 7 For other EU countries: 13
EIRP POWER (FOR DSSS)	18.97dBm (Measured Max. Average)
EIRP POWER (FOR OFDM)	17.63dBm (Measured Max. Average)
ANTENNA TYPE	PCB antenna with 0dBi gain
DATA CABLE	NA
I/O PORT	NA

NOTE:

1. This report is issued as a supplementary report of the original report (ADT report No.: SE941208L11). The main difference is changing the antenna.
2. The EUT will be installed in the platform: (1) Mobile Data Terminals (MDTs), (2) Vehicle Mounted Devices(VMDs).
3. The EUT, operates in the 2.4GHz frequency range, lets you connect IEEE 802.11g or IEEE 802.11b devices to the network. With its high-speed data transmissions of up to 54Mbps.
4. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3. RF Exposure Measurement

3.1 Introduction

This generic standard applies to low power electronic and electrical apparatus for which no dedicated product – or product family standard regarding human exposure to electromagnetic fields applies.

The frequency range covered is 10 MHz to 300 GHz.

The object of this standard is to demonstrate the compliance of such apparatus with the basic restrictions on exposure of the general public to electric, magnetic and electromagnetic fields and contact current.

3.2 Compliance criteria

All electromagnetic fields

If the average power emitted by the apparatus operating in the frequency range 10 MHz to 300 GHz is less than or equal to 20 mW and the transmitting peak power is less than 20 W then the apparatus is deemed to comply with the basic restrictions without testing. Averaging time is 6 minutes in the frequency range 10 MHz to 10 GHz. The average time is equal to $68/f^{1.05}$ minutes (where f is in GHz) in the frequency range 10 GHz to 300 GHz.

If the total supply power or the input power to the circuitry producing the greatest emissions in the device is less than or equal to 20 mW then it is assumed that the emitted power is less than 20 mW.

Pulse modulated electromagnetic fields with pulse duration less than 30 micro seconds

For pulse of duration less than 30 microseconds at frequencies between 300 MHz and 10 GHz, there is also a basic restriction on SA. This is 2mJ kg^{-1} in any 10g of tissue in the head. For most pulses, the SAR restriction will be more stringent, but for pulses with a repetition frequency of less than 100 Hz, the SA restriction will predominate. For devices producing pulses with repetition rates below 100 Hz, the average power should be less than $20 \times \text{prf}$ mW (prf in Hz).

3.3 EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.4 Test Results

FOR 802.11b DSSS MODULATION

Channel	Channel Frequency (MHz)	AV Power (EIRP)(mW) in EN300 328	Correct factor(dB)	AV Power (EIRP) (mW) in EN 50371	AV Power Limit (EIRP) (mW)	PASS/F AIL
1	2412	50.83	-7.21	9.66	20	PASS
4	2427	78.91	-7.21	14.99	20	PASS
7	2442	60.00	-7.21	11.40	20	PASS
13	2472	50.95	-7.21	9.68	20	PASS

FOR 802.11g OFDM MODULATION

Channel	Channel Frequency (MHz)	AV Power (EIRP)(mW) in EN300 328	Correct factor(dB)	AV Power (EIRP) (mW) in EN 50371	AV Power Limit (EIRP) (mW)	PASS/F AIL
1	2412	39.44	-7.21	7.49	20	PASS
4	2427	57.93	-7.21	11.01	20	PASS
7	2442	54.31	-7.21	10.32	20	PASS
13	2472	40.82	-7.21	7.76	20	PASS

NOTE:

1. According to EUT's specification, the compliance criteria item 2.1 shall be followed up.
2. Average power in EN 300 328 test report is measured under full load condition, so the average power shall be calibrated from the duty cycle.
The formula is average power +10 log(duty cycle)
3. Correct factor=10 log(duty cycle)
4. The duty cycle = 19 % is declared by manufacture under normal traffic load represents.